


# QSFP+ 40GBASE Passive Loopback Testing Module

QSFP-40G-LB-LL



## Application

- QSFP Port/System
- Server blade testing
- ITU-T Recommendation G.957 (STM-1, 4 & 16)
- Ethernet IEEE 802.3 (Gigabit, 10 Gigabit and 40 Gigabit Ethernet)
- SDR, DDR and QDR
- SONET, SDH, GBE, FC Support, Infiniband

## Features

- Customizable power consumption
- Custom memory maps available
- Supports 40Gbps total data rate
- Hot-pluggable MSA footprint
- Full SFF-8436 MSA compliant
- Temperature range from 0°C to 80°C
- Compliant with SONET, SDH, GBE, Fiber Channel
- MSA Compliant EEPROM
- Power Consumption Different Option
- Internal Attenuation Different Option


## Description

QSFP/QSFP+ Passive Electrical Loopback is used for testing QSFP/QSFP+ transceiver ports in board level test. By substituting for a full-featured QSFP/ QSFP+ transceiver, the electrical loopback provides a cost-effective low loss method for QSFP/QSFP+ port testing. The loopback module is packaged in a standard MSA housing compatible with all QSFP/QSFP+ ports. Transmit data from the host is electrically routed, (internal to the loopback module), to the receive data outputs and back to the host. It provides an economical way to exercise QSFP/QSFP+ ports during R&D validation, production testing, and field testing.


## Product Specifications

### I. Recommended Operation Condition


Parameter	Symbol	Min	Typ.	Max	Units	Notes/Conditions
<b>Operating Temperature</b>	TA	-20		85	° C	
<b>Supply Voltage</b>	VCC	3.15	3.3	3.45	V	Main Supply Voltage
<b>Data Rate</b>		0		40	Gbps	Guaranteed to work at 10.3125Gbps per lane
<b>Input/ Output Load Resistance</b>	RL	90	100	110	Ω	
<b>Durability Cycles</b>			100		Times	
<b>Power Level 0</b>				0	W	0 A
<b>Power Level 1</b>				1	W	0.3 A
<b>Power Level 2</b>				1.5	W	0.45 A
<b>Power Level 3</b>				2	W	0.60 A
<b>Power Level 4</b>				2.5	W	0.75 A
<b>Power Level 5</b>				3	W	0.91 A



**SDD12-0dB (Transmit Insertion Loss)**




**SDD21-3.5dB (Transmit Insertion Loss)**



SDD21-5dB (Transmit Insertion Loss)

## II. Host Board Connector Pinout

Figure 1: MSA compliant Connector



**Figure 2: Pin Definitions**


Pin	Logic	Symbol	Name/Description
1		GND	Ground
2	CML-I	Tx2n	Transmitter Inverted Data Input
3	CML-I	Tx2p	Transmitter Non-Inverted Data output
4		GND	Ground
5	CML-I	Tx4n	Transmitter Inverted Data Input
6	CML-I	Tx4p	Transmitter Non-Inverted Data output
7		GND	Ground
8	LVTTLL-I	ModSelL	Module Select
9	LVTTLL-I	ResetL	Module Reset
10		VccRx	+3.3V Power Supply Receiver
11	LVCNOS-I/O	SCL	2-Wire Serial Interface Clock
12	LVCNOS-I/O	SDA	2-Wire Serial Interface Data
13		GND	Ground
14	CML-O	Rx3p	Receiver Non-Inverted Data Output
15	CML-O	Rx3n	Receiver Inverted Data Output
16		GND	Ground
17	CML-O	Rx1p	Receiver Non-Inverted Data Output

18	CML-O	Rx1n	Receiver Inverted Data Output
19		GND	Ground
20		GND	Ground
21	CML-O	Rx2n	Receiver Inverted Data Output
22	CML-O	Rx2p	Receiver Non-Inverted Data Output
23		GND	Ground
24	CML-O	Rx4n	Receiver Inverted Data Output
25	CML-O	Rx4p	Receiver Non-Inverted Data Output
26		GND	Ground
27	LVTTL-O	ModPrsL	Module Present
28	LVTTL-O	IntL	Interrupt
29		VccTx	+3.3 V Power Supply transmitter
30		Vcc1	+3.3 V Power Supply
31	LVTTL-I	LPMode	Low Power Mode
32		GND	Ground
33	CML-I	Tx3p	Transmitter Non-Inverted Data Input
34	CML-I	Tx3n	Transmitter Inverted Data Output
35		GND	Ground
36	CML-I	Tx1p	Transmitter Non-Inverted Data Input
37	CML-I	Tx1n	Transmitter Inverted Data Output
38		GND	Ground

### III. Memory Map

The memory map is structured as a single address and multiple page approaches, according to the QSFP+ SFF-8436 MSA specification as shown in the below. For more detailed description of this memory map or lower pages, please see our Memory Map document with flexible customization settings.

**Table 1: Memory Map (Specific Data Field Descriptions)**



**Table 2: EEPROM Serial ID Memory Contents (Page00)**

Part Number		QSFP-LB-LL		
Device 0x Page00				
DATA Address (DEC)	DATA Address (HEX)	Value (HEX)	Name of Field	Description
128	80	0x0D	Identifier	QSFP+
129	81	0x00	Ext. Identifier	
130	82	0x80	Connector Type	Vendor Specific
131	83	0x80		40GBASE-CR4
132	84	0x00		
133	85	0x00		
134	86	0x00		
135	87	0x41	Specification Compliance	Intermediate distance (I) Medium (M) Electrical inter-enclosure (EL)
136	88	0x80		Electrical intra-enclosure
137	89	0x80		Twin Axial Pair (TW)
138	8A	0xF5		Fibre Channel Speed
139	8B	0x05	Encoding	64B/66B
140	8C	0xFF	BR, Nominal	10.3GBs
141	8D	0x00	Rate Select Compliance	Unspecified
142	8E	0x00	Length (SMF)	Unspecified
143	8F	0x00	Length (OM3 50um)	Unspecified
144	90	0x00	Length (OM2 50um)	Unspecified



145	91	0x00	Length (OM1 62.5um)	Unspecified
146	92	0x00	Cable Assembly Length (Copper or active cable)	Unspecified
147	93	0x80	Device Technology	Transmitter technology
148	94	0x31		
149	95	0x30		
150	96	0x47		
151	97	0x74		
152	98	0x65		
153	99	0x6B		
154	9A	0x20		
155	9B	0x20		
156	9C	0x20		
157	9D	0x20		
158	9E	0x20		
159	9F	0x20		
160	A0	0x20		
161	A1	0x20		
162	A2	0x20		
163	A3	0x20		
164	A4	0x00	Extended Module Code Values	Unspecified

165	A5	0x00		
166	A6	0x00	Vendor OUI	Unspecified
167	A7	0x00		
168	A8	0x43		
169	A9	0x41		
170	AA	0x42		
171	AB	0x2D		
172	AC	0x51		
173	AD	0x53		
174	AE	0x46		
175	AF	0x50		
176	B0	0x2D		
177	B1	0x4C		
178	B2	0x42		
179	B3	0x30		
180	B4	0x20		
181	B5	0x20		

182	B6	0x20		
183	B7	0x20		
184	B8	0x30		
185	B9	0x31	Vendor Rev	01
186	BA	0x00	Wavelength or Copper cable Attenuation	
187	BB	0x00		
188	BC	0x00	Wavelength Tolerance or Copper Cable Attenuation	Unspecified
189	BD	0x00		
190	BE	0x55	Max case Temp.	85°C
191	BF	0x00	CC_BASE	
192	C0	0x0B	Link Codes	100GBASE-CR4
193	C1	0x00		
194	C2	0x00	Options	Unspecified
195	C3	0x00		
196	C4	0x53		
197	C5	0x31		
198	C6	0x38		

199	C7	0x30		
200	C8	0x38		
201	C9	0x30		
202	CA	0x31		
203	CB	0x30		
204	CC	0x30		
205	CD	0x30		
206	CE	0x31		
207	CF	0x20		
208	D0	0x20		
209	D1	0x20		
210	D2	0x20		
211	D3	0x20		
212	D4	0x31		
213	D5	0x38		
214	D6	0x30		
215	D7	0x38		
216	D8	0x30	Date Code	180801
217	D9	0x31		
218	DA	0x20		
219	DB	0x20		

220	DC	0x00	Diagnostic Monitoring Type	Unsupported
221	DD	0x00	Enhanced Options	Unspecified
222	DE	0x00	BR, nominal	Unspecified
224	E0		CC_EXT	
225	E1			
226	E2			
227	E3			
228	E4			
229	E5			
230	E6			
231	E7			
232	E8			
233	E9		Vendor Specific	Unspecified
234	EA			
235	EB			
236	EC			
237	ED			
238	EE			
239	EF			
240	F0			
241	F1			

242	F2		
243	F3		
244	F4		
245	F5		
246	F6		
247	F7		
248	F8		
249	F9	Vendor Specific	Unspecified
250	FA		
251	FB		
252	FC		
253	FD		
254	FE		
255	FF		

### IV. Mechanical Specifications

